

BioClad

NS Plus



PVC Hygienic Wall Cladding

By BioClad

Detailed description

A high quality, virgin PVC wall cladding system for almost any environment. It is compatible with standard trims and details, can be welded and thermoformed. Advanced PVC cladding panels don't harbour bacteria like tiles do and can be wiped clean in seconds.

Typical applications:

Food manufacturing areas, commercial kitchens, pharmaceutical areas, laboratories, showers, W.C.'s and wet hygienic areas.

Suitable substrates:

- Good quality fair faced brick or blockwork.
- Sand and cement rendering 1:3 with a steel trowel finish.
- 12.5 mm thick plasterboard.
- Ceramic tiles which are securely bonded to substrate.
- 9 mm (minimum) W.P.B resin bonded to substrate.
- Pink lightweight plasters are generally not suitable.
- Some surfaces may need PVA sealer subject to site survey.

Product guidance - As Standard

Fire rating to BS 476-7:1971:

Class 0 (when bonded to a non combustible substrate).

Colour:

White.

Method of fixing:

Fixed using PVC Silicone free gasket system or Advanced welded joints and Advanced all over adhesive.

Components:

Site thermoformed angle sections internal/ external corners, UPVC cill details, joints and edge trims. As specified BS "foodsafes" complying with EEC regulations for hygiene in for production areas. Directive No 64/483 and the requirement asoutlined in statutory instruments 454 and 805 (food hygiene).

Product specification

Manufacturer

- Name: BioClad
- Web: www.bioclad.com
- Email: sales@bioclad.com
- Tel: +44 (0)330 100 0313
- Fax: +44 (0)330 100 1314
- Address: Unit A1, Greengate, Cardale Park, Harrogate, North Yorkshire HG3 1GY

Product reference Advanced PVC Hygienic Wall Cladding

Size (w x h) 1220 x 2400 mm
 1220 x 3000 mm

Thickness 2.5 mm - Manufacturer's standard

Colour White

Joints Advanced Two Part 'H' Section / Advanced Hot Welded Joint